PARAFON Hygiene Baffle







Short Description

PARAFON Hygiene baffle is a vertically suspended acoustic tile of non-combustible mineral wool enclosed in a 0.1 mm white, UVstabilised polyethylene film developed for premises with extremely high requirements for good hygiene and cleaning and can withstand rinsing with a low-pressure jet.

Usage Conditions

May be used continuously in 95 % relative humidity at a temperature of 30 \degree C, occasionally also at 100 % and 40 \degree C.

Dimensions

Dimensions		
Thickness	Width x Length	Weight
Edge A:		
50 mm	600 x 1200 mm	2,0 kg/pc

Packaging

Package Type

Carton

Fire Properties

Reaction to Fire		
Property	Value	According to
Reaction to Fire, Euroclass	F	EN 13964:2014 (EN 13501-1)

Other Fire Properties		
Property	Value	According to
Combustibility	Base product non-combustible	EN ISO 1182

Sound absorption is measured as absorption surface/baffle (m² Sabine), see tab Acoustics.

Mechanical Properties

Paroc Group © 2020



Tensile/Flexural Strength		
Property	Value	According to
Flexural Tensile Strength	NPD	EN 13964:2014

Other Mechanical Properties		
Property	Value	According to
Shatter Properties	NPD	EN 13964:2014

Emissions

Property	Value	According to
Emission Indoor Climate	M1	Finnish Classification

Release of Dangerous Substances to the Indoor Envi	ronment	
Property	Value	According to
Release of Formaldehyde	E1	EN 13964:2014
Release of Asbestos	No content of asbestos	EN 13964:2014

Durability

Durability of Reaction to Fire Against Heat, Weathering	g, The fire performance of mineral wool
Ageing/Degradation	does not deteriorate with time. The
	Euroclass classification of product is
	related to the organic content, which
	cannot increase with time.

Facings

Facing Material

Consists of a acoustic stone wool tile entirely contained in a 0.1 mm, white, UV-stabilized polyethylene foil.

Colours

White, NCS S 1000-N

Installation

Can be suspended with the appropriate cable and in two supplied stainless steel bracket mounts.

Maintenance

Using a soft brush, by vacuum cleaning or by wiping with a damp cloth or sponge. May be washed by low pressure, see instructions.

Disposal and Recycling

May be used as thermal insulation or taken to a dump. No restrictions.

Sound Absorption Curves

Updated: 24.06.2019 Printed: 09.01.2020



Veighed absorpt		or and		dreed sou c		
hickness 50 mm Veighed absorpt annot be specifie		or and	00101	seen c	1315	
			abaaaa	_	-	
63 125	250	500	1000		0 400	
.2	+	+	+	+	-	
14	-	+	+	+	-	
2,6	/	+	+	+	\geq	
.8	1	-	-	X	_	
.0	-	\vdash			_	
2		-		_		
biorption area i	w.ml	(m2 S	hinal			
200x000x3	0 mm,	HAN	IGIN	G		
200x600x5I						

.

Head Office: PAROC GROUP, P.O. Box 240 (Energiakuja 3), FI-00181 Helsinki Finland, Tel. +358 46 876 8000, www.paroc.com

The information in this brochure describes the conditions and technical properties of the disclosed products, valid at the time of publication of this document and until replaced by the next printed or digital version. The latest version of this brochure is always available on the Paroc website. Our information material presents applications for which the functions and technical properties of our products have been approved. However, the information does not mean a commercial guarantee. We do not assume liability of the use of third party components used in the application of our products. We cannot warrant the suitability of our products if used in an area or conditions which are not provided in our information material at any time. PAROC is a registered trademark of Paroc Group. This data sheet is valid in following countries: international use (general information).