Updated: 20.06.2019 Printed: 09.01.2020

Prelude T-35 XL²







Short Description

Suspended ceilings. Exposed 35 mm T-grid system (nominal). For use in large shed type buildings including retail outlets, industrial manufacturing and meeting halls, etc.

Dimensions

Dimensions	
Width x Length	Height
Universal Main runner Prelude 15 Peakform:	
35 x 3600 mm (Galv, White)	38 mm
Cross tee Prelude 15 XL2:	
35 x 1200 mm (Galv, White)	38 mm
35 x 600 mm (Galv, White)	38 mm
Perimeter trim:	
22 x 3000 mm (White)	22 mm
Shadowline:	
(15+15) x 3050 mm (White)	(8 + 25) mm

Packaging

Package Type Carton

Fire Properties

Reaction to Fire				
Property	Value	According to		
Reaction to Fire, Euroclass	A1	EN 13964:2014		

Mechanical Properties

Other Mechanical Properties		
Property	Value	According to
Durability	Corrosion protection class B	EN 13964:2014

Facings

Facing Material Baked polyester paint

Paroc Group © 2020

Updated: 20.06.2019 Printed: 09.01.2020



Colours

Global white, nearest RAL 9003/NCS 0502-B, Galvanized (UP)

Maintenance

Clean with mild household cleaner and a soft cloth. Before cleaning the grid remove the ceiling tiles to prevent cleaning solution or dirt from getting on the tiles.

Paroc Group © 2020 2(2)